



BARE BONES™

No Rinse / No Scrub Liquifying Stripper

DESCRIPTION

A 55% active speed stripper that easily cuts through multi-layers of burnished floor finish. This "true" no rinse stripper does not contain potassium hydroxide or sodium hydroxide yet is the fastest working liquifier on the market. Low foaming, no scrub and no rinse features make this product a must for all professional floor care systems.

PRODUCT FEATURES / BENEFITS

- Low foaming / Can be used through automatic scrubbers
- Contains no potassium or sodium hydroxide / Safe for personnel & flooring
- Requires no rinsing / Saves time by eliminating neutralizing and rinsing
- No scrubbing machine needed / Reduces equipment costs & can be used in hard to get to places
- 55% Active / High use dilution for greater economy

DIRECTIONS FOR USE

For the rapid removal of all floor finishes and waxes from resilient flooring including: vinyl, vinyl asbestos, vinyl composition, asphalt, linoleum, and rubber tiles. Also ideal for finished nonresilients such as: terrazzo, marble, ceramic, quarry tile, ceramic, quarry tile, concrete, and poured epoxy flooring. Although excellent for any type of equipment, greatest savings are realized when using automatic scrubbing equipment.

Mop/Wet Vacuum Stripping System:

Dilute in cold or mildly warm water from one part product to 2 parts water for heavily built-up or highly burnished finishes, to one part product to five parts water for normal build up. Apply liberally with a mop to an area small enough so as not to allow the product to dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete

stripping is not accomplished repeat above procedure before re-application of new finish.

Floor Machine Stripping System:

Dilute and apply product as above using a dilution of 1 part product to 16 parts water varying according to build-up conditions. Product may be applied with a mop or Automatic Scrubber. Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply new finish per manufacturer's recommendation.

Note: As some asphalt tiles may be damaged by prolonged soaking in concentrated strippers, a spot test is recommended before general use.

SPECIFICATIONS

Color Clear
 Odor Sassafras
 pH 11.3 ± .3
 Flash Point None to Boiling
 Upper Cloud Point Below 130° F
 Lower Cloud Point Above 33° F
 Viscosity 5 cps max.
 Water Solubility Complete

Shelf Life 1 Year Minimum
 Finish Removal Excellent
 Damage to Resilient Tiles Minimal
 Density (lbs./gal.) 8.07 ± 0.1
 Specific Gravity 0.97
 Free Rinsing Yes
 Low Foaming Yes

SAFETY INFORMATION

WARNING: IRRITANT. MAY BE HARMFUL IF SWALLOWED. Avoid contact with skin, eyes and clothing. Do not ingest.

For Eyes: Flush thoroughly with water for 15 minutes. Get medical aid.

For Skin: Wash thoroughly with soap and water. If irritation persists, get medical aid.

If ingested: Do not induce vomiting. Give water, milk, egg white, or gelatin. Get medical advice.

For sale to, use and storage by Service Personnel only.



STRIPPERS



National Chemical Laboratories, Inc.
World Class Cleaning Solutions®

401 N. 10th Street · Philadelphia, PA 19123
1-800-NAT-CHEM · 215-922-1200 · FAX: 215-922-5517
www.nclonline.com · e-mail:sales@nclonline.com

TDS-1058-0106