



IMPRESSIONS™

Brilliant Gloss / Ultra Wear Floor Finish

DESCRIPTION

A proprietary blend of synergistic polymers provide uncompromised benefits of immediate wet look gloss and outstanding wearability. Sophisticated integrated components allow for rapid drying, enhanced leveling and superior repairability. This versatile product can be used in many varied environments and maintained with both high & low speed equipment.

PRODUCT FEATURES / BENEFITS

- Very hard wear surface / Extremely scuff resistant
- Enhanced leveling; repairs easily / Usable by any personnel in many applications
- Super brilliant gloss / Maximizes appearance & user appeal
- Fast drying / Allows faster recoating and less waiting
- Pure thermoplastic polymers / Very responsive to multi-speed polishing

DIRECTIONS FOR USE

A proprietary blend of synergistic polymers provide uncompromised benefits of immediate wet look gloss and outstanding wearability. Sophisticated integrated components allow for rapid drying, enhanced leveling and superior repairability. This versatile product can be used in many varied environments and maintained with both high & low speed equipment.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be recoated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

Floor Preparation: Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly with clean water and allow to completely dry. Application: If desired one or two coats of an approved sealer may be used, prior to finish application. Using a clean mop or applicator apply a thin uniform coat of finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24

hour period. Floor should be thoroughly dry before traffic is allowed in area. Spray Buff: To restore original luster, polish with an approved spray buff compound or laminator.

High Speed Burnishing: This is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. The floor should first be damp mopped with a suitable neutral cleaner and allowed to dry. The surface may then, as desired, be dry burnished with a high speed white or tan buffing pad, or using the same equipment, be spray buffed using an approved product. An alternate method, for insuring a long lasting durable surface, would be to apply an approved mop-on restorer or laminator, allow to dry and then to follow the dry buffing procedure. Floor finish can also be polished by auto scrub method.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be recoated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

SPECIFICATIONS

Type	Pure acrylic polymers
Solids	21 ± .5%
pH	8.5 - 9.5
Coverage	2500 sq. ft./gal
Drying Time	20-30 minutes
Color	White, opaque liquid
Odor	Acrylic
Film Appearance	Clear
Powdering	None
Flash Point	None
Freeze thaw stable	Yes (3 Freeze Thaw Cycles)

Detergent Resistant	Yes
Multi-Speed Buffing	Yes
Leveling	Excellent
Black Mark Resistant	Superior
Scuff Resistance	Superior
Soil Resistance	Superior
Durability	Excellent
Recoatibility	Excellent
Removability	Excellent
Immediate Wet Look Gloss	Outstanding
Slip Resistant	Yes
Shelf Life	1 year in original unopened container

SAFETY INFORMATION

CAUTION: May Be Harmful If Swallowed. Keep out of reach of children. Avoid eye contact. Do not ingest.

For Eyes: Flush with water for 15 minutes. Get medical aid.

If Ingested: Do not induce vomiting. Give water. Get medical aid. Keep from freezing.

For sale to, use and storage by Service Personnel only.



FLOOR CARE



CLASSIFIED BY
UNDERWRITERS LABORATORIES INC.®
AS TO SLIP RESISTANCE ONLY. 18EL



National Chemical Laboratories, Inc.
World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:sales@nclonline.com

TDS-0550-0106