



# WITHSTAND

Non-Buff Maximum Wear  
Sealer / Finish

## DESCRIPTION

This superior sealer / finish is ideal for areas which receive little to no polishing or buffing. Utilizing MPS77 Advanced Technology, WITHSTAND provides a dramatic wet-look gloss from fewer coats, with long term gloss retention. Easy to apply; reduces labor costs. Classified by Underwriters Laboratories® for slip resistance.

## PRODUCT FEATURES / BENEFITS

- High Traffic Applicable
- Exceptional wear and durability
- Combination Sealer/Finish reduces product cost
- Maximum scuff and scratch resistance
- Reduces labor costs associated with buffing maintenance

## DIRECTIONS FOR USE

### Floor Preparation:

Using **BARE BONES, No-Rinse, No-Scrub Liquifying Stripper**, strip off old finish and wax, paying particular attention to areas under furniture, and build-up areas. For baseboards and corners, use **PIZZAZZ Baseboard Stripper**. Remove all stripping solutions from floor with mop or wet dry vacuum. If necessary, rinse thoroughly with clean water and allow to completely dry.

### Application:

Using a clean mop or applicator apply a thin uniform coat of **WITHSTAND Non-buff Floor Sealer/Finish**. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

**High Speed Buffing and Burnishing (if desired):** WITHSTAND is an ideal product for use in areas where minimal or no buffing maintenance can be performed. You may, if desired, maintain this product with high speed polishing or UHS burnishing equipment

(electric, battery or propane). Conventional speed maintenance is not recommended. Prior to high speed buffing or UHS burnishing, the floor surface should be dust mopped using **CONTROL Dust Mop Treatment**. When buffing or dry burnishing, an aggressive natural hair burnishing pad is recommended. For spray buffing and for mop-on restoring use **POP & SHINE Gloss Restorer** according to label instructions.

### Maintenance:

Maintain by dust mopping daily using mop treated with **CONTROL Dust Mop Treatment**. Damp mop or clean with an automatic scrubber as required, using recommended NCL Neutral Floor Cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended using **POP & SHINE Gloss Restorer**. Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary, use **BARE BONES No-Rinse, No-Scrub Stripper**.

## SPECIFICATIONS

Type..... Pure acrylic polymers  
 Total Solids (%).....23 ± 0.5  
 pH.....8.5 ± 0.5  
 Coverage (sq. ft./gal).....2,500  
 Drying Time (minutes).....30  
 Color..... White, opaque liquid

Odor..... Typical acrylic  
 Film Appearance..... Clear  
 Powdering..... None  
 Flash Point..... None  
 Slip Resistant..... Yes  
 Shelf Life..... 1 year minimum in original unopened container

## SAFETY INFORMATION

**CAUTION:** MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with eyes. Do not ingest. If ingested, may cause severe gastric distress and blockage.

**FIRST AID: For Eyes:** Flush thoroughly with water for at least fifteen minutes. If irritation persists seek medical attention. **For Skin:** Wash thoroughly with soap and water. If irritation persists seek medical attention. **If ingested:** Do not induce vomiting.

Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

KEEP FROM FREEZING  
FOR PROFESSIONAL USE ONLY



FLOOR CARE



Floor Finish and Finishing Material  
As to Slip Resistance Only 18EL

| HMIS HAZARD CODE |                     |
|------------------|---------------------|
| 1                | HEALTH              |
| 0                | FLAMMABILITY        |
| 0                | REACTIVITY          |
| 0                | PERSONAL PROTECTION |



National Chemical Laboratories, Inc.  
World Class Cleaning Solutions®

401 N. 10th Street · Philadelphia, PA 19123  
1-800-NAT-CHEM · 215-922-1200 · FAX: 215-922-5517  
www.nclonline.com · e-mail:info@nclonline.com